# 162

### **LUMINOUS BOWL**





print this page



<u>≡</u> email this page to a colleague



installation instructions



interactive submittal drawing

#### **COMPANION**





## **FEATURES**

- Simple clean design.
- Luminous bowl with downlight component.
- Tool-free relamping.

#### **ECO INFO**

Shown in Satin Aluminum

METALS: Aluminum and brass with the highest available recycled content for lower embodied energy. Both metals are valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO"

FINISHING: Aluminum and Anitque Brass finishes are sealed with a hand-applied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Satin Brass is clear-coated with a very low VOC water-based coating. Paint finishes are low VOC and oven cured.

**ENERGY:** Designed exclusively for compact fluorescent lamps using HPF electronic ballasts.

#### **MATERIALS**

- Solid brass or aluminum metal work, hand finished
- Luminous bowl is white acrylic with a matte finish.

#### **FINISHES**

SAL Satin Aluminum

**SB** Satin Brass

**AB** Antique Brass

**CCP** Custom Color Painted finish

Standard metal finishes are hand satined and either waxed. or sealed with a water-based clear coat. Other metal finishes are available. Contact factory.

#### **LAMPING**

1-CF26W or 32WTTT, Gx24q base. Lamp not included.

#### **BALLAST**

Integral electronic HPF, 120V/277V. See "GENERAL INFO" for more detail.






Shown with optional faux finish

#### **OPTIONS**

FAUX: Hand applied faux finish available.


**EMERGENCY BATTERY PACK:** Remote mounted EBP, specify **REM**.

# 162



# **PHOTOMETRICS**Lighting Sciences Report 22413

Fixture Efficiency: 84.2%



#### **VARIATIONS / MODIFICATIONS**

- Special finishes
- Addition of decorative detail
- Different bowl size

**NOTE:** Standard electronic ballast is multi-volt and multi-wattage. Fixture will accommodate 26 or 32 watt lamps.

**MOUNTING:** Standard J-box or plaster ring.

**WEIGHT:** 5 lbs

# SPEC GUIDE SAMPLE SPEC: 162-CF1/26-120 -SAL-FAUX

CAT# -LAMPING OPTION V0LT FINISH **1**62 ☐ CF1/26 **□** 120 □ SAL ☐ FAUX ☐ CF1/32 **2**77 □ SB ☐ REM □ 120DIM □ AB ☐ CCP



