





# **FABRIC SCONCE**





print this page



<u>≡</u> email this page to a colleague



installation instructions



interactive submittal drawing

### COMPANIONS





- Purpose-built for LED
- Fabric laminated to acrylic and is washable.



## **ECO INFO**

**METALS:** Aluminum parts have the highest available recycled content for lower embodied energy. All metals are valuable and recyclable at the end of the product's useful life.

For more information see "GENERAL INFO"

FINISHING: Solid, natural metal finishes are sealed with a hand-applied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Clear coat finishes are available. Paint finishes are low VOC and oven cured.

**ENERGY:** Designed exclusively for LEDs using HPF electronic drivers.

### **MATERIALS**

• Fabric and acrylic

## **LAMPING**

1-10W LED array, 1060 lumens, 3000K, 80+ CRI


### **Driver**

Integral HPF electronic driver is 120 volt and is triac dimmable. 0-10V dimming available for 120 & 277V.






# **501**





#### **PHOTOMETRICS**

Lighting Sciences Report No. L091404204 Fixture Efficiency: 59 lm/w



### **OPTIONAL FABRICS:**



**MOUNTING:** Standard J-box or plaster ring **WEIGHT:** 4 lbs

## **VARIATIONS / MODIFICATIONS**

- Special finishes
- · Addition of decorative detail

**NOTE:** Integral HPF electronic driver is 120 volt and is triac dimmable. 0-10V dimming available for 120 & 277V.

# **SPEC GUIDE** SAMPLE SPEC: 501-LED1/10-120

