

UPDATED 8/15

915 NEW LED

INDIRECT BOLLARD WITH LUMINOUS POST





 $\equiv \boxed{}$ email this page to a colleague

installation instructions

interactive submittal drawing





Showing broad distribution and luminous post.

FEATURES

- Unique luminous post.
- Purpose-built for indirect LED.
- Available for symetric or assymetric distribution.

MATERIALS

- Solid aluminum hood.
- Cast aluminum collar and base.
- Fabricated acrylic post, UV resistant.

FINISHES

SGB Semi-Gloss Black
SGW Semi-Gloss White
SGS Semi-Gloss Silver
SGBZ Semi-Gloss Bronze

CCP Custom Color Painted Finish

LAMPING

1-11W LED array, 1550 lumens or 1-16W, 2120 lumens, Both are 3000K, 80+ CRI. LED arrays are included and easily changed. One 3W array used to light the bollard.

DRIVER

Integral HPF electronic driver, 120/277 volt, 0-10V dimming. 2-wire triac dimming available for 120V.






Showing Asymetric Hood.

OPTIONS


For a "forward throw" (Type IV) distribution for pathway lighting, specific AH, Asymetric Hood.

NOTE: Luminous post can be wired on a separate circuit.

915 **INDIRECT BOLLARD**







SPEC GUIDE SAMPLE SPEC: 915-LED/10-120-SGW-36" 0A

CAT# - LAMPING -0A VOLT FINISH **9**15 ☐ LED/11 **1**20 □ 36" STD □SGB ☐ LED/16 **277** □ SGW □ SGBZ □ SGS ☐ CCP



