INDIRECT SHADE PENDANT





print this page





installation instructions



interactive submittal drawing



Shown in Satin Aluminum.



FEATURES

- Simple clean design.
- Purpose-built design for LED only.
- High efficacy and high CRI.
- Soft, diffuse indirect light.

ECO INFO

ENERGY: Designed exclusively for LEDs using HPF electronic drivers.

METALS: Aluminum with the highest available recycled content for lower embodied energy. Aluminum is valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO"

FINISHING: Aluminum finishes are sealed with a handapplied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Paint finishes are low VOC and oven cured.

MATERIALS

- White acrylic bowl.
- Spun aluminum hood.
- Aluminum heat sink disks.

FINISHES

SAL Satin Aluminum (Hand satined and waxed.)

MW Matte White

CCP Custom Color Painted finish

LAMPING

1-23W LED array; 2810 lumens, 3000K, 80 CRI and 122 LM/W. LED array is included and is easily replaceable.

DRIVER


Integral HPF electronic driver is multi-volt 120/277 and is 0-10V dimmable.





OPTIONS


STEM: Available with metal stem and swivel canopy, specify **STEM**.





PHOTOMETRICS

Light Lab Report L05131410
Tested LED rated at 2100lm; new
LED rated at 2810lm or 34% more.
Adjust light levels accordingly.



VARIATIONS / MODIFICATIONS

- Special finishes
- Addition of decorative detail

NOTE: Standard electronic driver is multi-volt and is 0-10V dimmable.

MOUNTING: Standard J-box or plaster ring.

WEIGHT: 8 lbs

SPEC GUIDE SAMPLE SPEC: 306-LED/24-120-SAL-24" OA

 CAT#
 LAMPING
 VOLT
 FINISH

 306
 IED/23
 120
 SAL

☐ 120 ☐ SAL ☐ MW ☐ CCP

OPTION

REM
STEM

□ 24" STD □ SPECIFY

0A





Our fixtures are handcrafted here in the USA using the highest quality materials.

