INDIRECT SHADE PENDANT



print this page



<u>≡</u> email this page to a colleague




installation instructions



interactive submittal drawing





FEATURES

- Simple clean design.
- Purpose-built design for LED only.
- High efficacy and high CRI.
- Soft, diffuse indirect light.

ECO INFO

ENERGY: Designed exclusively for LEDs using HPF electronic drivers.

METALS: Aluminum with the highest available recycled content for lower embodied energy. Aluminum is valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO"

FINISHING: Aluminum finishes are sealed with a handapplied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Paint finishes are low VOC and oven cured.

MATERIALS

- White acrylic bowl.
- Spun aluminum hood.
- Aluminum heat sink disks.

FINISHES

SAL Satin Aluminum (Hand satined and waxed.)

MW Matte White

CCP Custom Color Painted finish

LAMPING

1-16W LED array; 2415 lumens, 3000K, 80 CRI or 1-24W; 3180 lumens, 3000k, 80 CRI. LED array is included and is easily replaceable.

DRIVER


Integral HPF electronic driver is multi-volt 120/277 and is 0-10V dimmable.






OPTIONS

STEM: Available with metal stem and swivel canopy, specify **STEM**.



PHOTOMETRICS

Light Lab Report L05131410
Tested LED rated at 2100lm; new
LED rated at 3180lm or 50% more.
Adjust light levels accordingly.



VARIATIONS / MODIFICATIONS

- Special finishes
- Addition of decorative detail

NOTE: Standard electronic driver is multi-volt and is 0-10V dimmable.

MOUNTING: Standard J-box or plaster ring.

WEIGHT: 8 lbs

SPEC GUIDE SAMPLE SPEC: 306-LED/24-120-SAL-24" OA

CAT# - LAMPING **VOLT** FINISH OPTION 0A □ 306 ☐ LED/24 **1**20 □ SAL ☐ REM ☐ 24" STD ☐ LED/16 **2**77 □ MW □ STEM ☐ SPECIFY □ CCP



Our fixtures are handcrafted here in the USA using the highest quality materials.

IBEW Labelled

