

366 LED NEW

LUMINOUS GLOBE PENDANT





print this page



<u>≡</u> email this page to a colleague



installation instructions



interactive submittal drawing

COMPANIONS







FEATURES

- Classic globe re-imagined.
- Integral multi-volt, 0-10V dimming driver.
- Two high lumen LED light engines available.

ECO INFO

ENERGY: Designed exclusively for LEDs using integral electronic drivers.

METALS: Aluminum with the highest available recycled content for lower embodied energy. Aluminum is valuable and recyclable at the end of the product's useful life. For more information see "GENERAL INFO"

FINISHING: Aluminum finishes are sealed with a handapplied bees wax. No paint or lacquer is used in order to avoid pollution associated with the manufacture and application of these substances. Paint finishes are low VOC and oven cured.

MATERIALS

- White acrylic globe.
- Spun aluminum trim and canopy.
- Aluminum heat sink disks.

FINISHES

SAL Satin Aluminum (Hand satined and waxed.)

MW Matte White

CCP Custom Color Painted finish

LAMPING

3-9W LED arrays, total rated lumens of 3600 at 27W, or 3-11W, total rated lumens of 4650 at 33W.


All LEDs are 3000K, 80+CRI, are included and are easily replaceable.

DRIVER

Integral electronic HPF, 120/277V and is 0-10V dimmable.



366 LUMINOUS GLOBE PENDANT



OPTIONS


STEM: Available with metal stem and swivel canopy,

specify **STEM**.



PHOTOMETRICS

LightLab Report No. LLI-17203-2 92 lm/W Delivered lumens: 3440



MOUNTING: Standard J-box or plaster ring.

WEIGHT: 8 lbs

VARIATIONS / MODIFICATIONS

- Special finishes
- Addition of decorative detail

SPEC GUIDE SAMPLE SPEC: 366-LED3/9-277-SAL-36"0A

 CAT#
 LAMPING
 VOLT
 FINISH
 OPTION
 OA

 366
 LED3/9
 120
 SAL
 STEM
 24" STD

 MW
 CCP





Our fixtures are handcrafted here in the USA using the highest quality materials.

